



ENCAPSULATED TRANSFORMER 密封变压器								
FEATURES			产品特点					
. Frequency 50/60 Hz			. 频率: 50/60 Hz					
. Temperature Class Class B (130° C)			. 温度等级: B级 (130° C)					
. Ambient Temperature (ta) 70° C			. 环境温度: (ta) 70° C					
. Resins Class B IEC85 (20,000H Testing to IEC216)			. 胶温度等级: B级 附合IEC85标准 (通过 20,000小时 IEC216标准)					
. Vacuum Potting			. 真空灌胶					
. Flammability Class UL94 V-0			. 材料阻燃等级: UL94 V-0					
. Dielectric Strength 4200Vrms			. 介电强度: 4200Vrms					
. Standard VDE. UL. CUL. CE. CQC			. 标准: VDE. UL. CUL. CE. CQC					
. Conforms EN61558. EN60950. UL1585. UL506			. 符合EN61558. EN60950. UL1585. UL506					
. 200%Tested Production			. 产线200%全检					
OUTLINE DIMENSIONS 外形尺寸			ELECTRICAL SCHEMATIC 电气原理图					
								
EE20-10.5 SERIES 0.5VA								
Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
0.50VA	115	VB201S-06005	6	83	11.2	T 70 B	20	36
		VB201S-07005	7.2	69	12.2	T 70 B	20	36
		VB201S-09005	9	56	14.2	T 70 B	20	36
		VB201S-12005	12	42	19.2	T 70 B	20	36
		VB201S-15005	15	33	24.2	T 70 B	20	36
		VB201S-18005	18	28	28.2	T 70 B	20	36
		VB201S-24005	24	21	38.2	T 70 B	20	36
		VB201D-06005	2×6	2×42	2×11.2	T 70 B	20	36
		VB201D-07005	2×7.2	2×36	2×12.2	T 70 B	20	36
		VB201D-09005	2×9	2×28	2×14.2	T 70 B	20	36
		VB201D-12005	2×12	2×21	2×19.2	T 70 B	20	36
		VB201D-15005	2×15	2×17	2×24.2	T 70 B	20	36
0.50VA	230	VB201D-18005	2×18	2×14	2×28.2	T 70 B	20	36
		VB202S-06005	6	83	11.2	T 70 B	20	36
		VB202S-07005	7.2	69	12.2	T 70 B	20	36
		VB202S-09005	9	56	14.2	T 70 B	20	36
		VB202S-12005	12	42	19.2	T 70 B	20	36
		VB202S-15005	15	33	24.2	T 70 B	20	36
		VB202S-18005	18	28	28.2	T 70 B	20	36
		VB202S-24005	24	21	38.2	T 70 B	20	36
		VB202D-06005	2×6	2×42	2×11.2	T 70 B	20	36
		VB202D-07005	2×7.2	2×36	2×12.2	T 70 B	20	36
		VB202D-09005	2×9	2×28	2×14.2	T 70 B	20	36
		VB202D-12005	2×12	2×21	2×19.2	T 70 B	20	36
0.50VA	400	VB202D-15005	2×15	2×17	2×24.2	T 70 B	20	36
		VB202D-18005	2×18	2×14	2×28.2	T 70 B	20	36
		VB203S-06005	6	83	11.2	T 70 B	20	36
		VB203S-07005	7.2	69	12.2	T 70 B	20	36
		VB203S-09005	9	56	14.2	T 70 B	20	36
		VB203S-12005	12	42	19.2	T 70 B	20	36
		VB203S-15005	15	33	24.2	T 70 B	20	36
		VB203S-18005	18	28	28.2	T 70 B	20	36
		VB203S-24005	24	21	38.2	T 70 B	20	36
		VB203D-06005	2×6	2×42	2×11.2	T 70 B	20	36
		VB203D-07005	2×7.2	2×36	2×12.2	T 70 B	20	36
		VB203D-09005	2×9	2×28	2×14.2	T 70 B	20	36

ENCAPSULATED TRANSFORMER 密封变压器


FEATURES

- Frequency 50/60 Hz
- Temperature Class Class B (130° C)
- Ambient Temperature (ta) 70° C
- Resins Class B IEC86 (20,000H Testing to IEC216)
- Vacuum Potting
- Flammability Class UL94 V-0
- Dielectric Strength 4200Vrms
- Standard VDE. UL. CUL. CE. CQC
- Conforms EN61558. EN60950. UL1585. UL506
- 200%Tested Production


产品特点

- 频率: 50/60 Hz
- 温度等级: B级 (130° C)
- 环境温度: (ta) 70° C
- 胶温等级: B级 符合IEC86标准 (通过 20,000小时 IEC216标准)
- 真空灌胶
- 材料阻燃等级: UL94 V-0
- 介电强度: 4200Vrms
- 标准: VDE. UL. CUL. CE. CQC
- 符合EN61558. EN60950. UL1585. UL506
- 产线200%全检



OUTLINE DIMENSIONS 外形尺寸



ELECTRICAL SCHEMATIC 电气原理图



EI30-5 SERIES 0.6VA								
Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
0.6VA	115	VB301S-06006	6	100	10.5	T 70 B	16	41.5
		VB301S-07006	7.2	83	12.6	T 70 B	16	41.5
		VB301S-09006	9	66	15.5	T 70 B	16	41.5
		VB301S-10006	10	60	16	T 70 B	16	41.5
		VB301S-12006	12	50	20.5	T 70 B	16	41.5
		VB301S-15006	15	40	25.4	T 70 B	16	41.5
		VB301S-18006	18	33	30.4	T 70 B	16	41.5
		VB301S-24006	24	25	40.4	T 70 B	16	41.5
		VB301D-06006	6	2x50	2x10.5	T 70 B	16	41.5
		VB301D-07006	7.2	2x42	2x12.6	T 70 B	16	41.5
		VB301D-09006	9	2x33	2x15.5	T 70 B	16	41.5
		VB301D-10006	10	2x30	2x16	T 70 B	16	41.5
		VB301D-12006	12	2x25	2x20.5	T 70 B	16	41.5
		VB301D-15006	15	2x20	2x25.0	T 70 B	16	41.5
		VB301D-18006	18	2x17	2x30.4	T 70 B	16	41.5
	230	VB302S-06006	6	100	10.5	T 70 B	16	41.5
		VB302S-07006	7.2	83	12.6	T 70 B	16	41.5
		VB302S-09006	9	66	15.5	T 70 B	16	41.5
		VB302S-10006	10	60	16	T 70 B	16	41.5
		VB302S-12006	12	50	20.5	T 70 B	16	41.5
		VB302S-15006	15	40	25.4	T 70 B	16	41.5
		VB302S-18006	18	33	30.4	T 70 B	16	41.5
		VB302S-24006	24	25	40.4	T 70 B	16	41.5
		VB302D-06006	6	2x50	2x10.5	T 70 B	16	41.5
		VB302D-07006	7.2	2x42	2x12.6	T 70 B	16	41.5
		VB302D-09006	9	2x33	2x15.5	T 70 B	16	41.5
		VB302D-10006	10	2x30	2x16	T 70 B	16	41.5
		VB302D-12006	12	2x25	2x20.5	T 70 B	16	41.5
		VB302D-15006	15	2x20	2x25.0	T 70 B	16	41.5
		VB302D-18006	18	2x17	2x30.4	T 70 B	16	41.5
	400	VB303S-06006	6	100	10.5	T 70 B	16	41.5
		VB303S-07006	7.2	83	12.6	T 70 B	16	41.5
		VB303S-09006	9	66	15.5	T 70 B	16	41.5
		VB303S-10006	10	60	16	T 70 B	16	41.5
		VB303S-12006	12	50	20.5	T 70 B	16	41.5
		VB303S-15006	15	40	25.4	T 70 B	16	41.5
		VB303S-18006	18	33	30.4	T 70 B	16	41.5
		VB303S-24006	24	25	40.4	T 70 B	16	41.5
		VB303D-06006	6	2x50	2x10.5	T 70 B	16	41.5
		VB303D-07006	7.2	2x42	2x12.6	T 70 B	16	41.5
		VB303D-09006	9	2x33	2x15.5	T 70 B	16	41.5
		VB303D-10006	10	2x30	2x16	T 70 B	16	41.5
		VB303D-12006	12	2x25	2x20.5	T 70 B	16	41.5
		VB303D-15006	15	2x20	2x25.0	T 70 B	16	41.5
		VB303D-18006	18	2x17	2x30.4	T 70 B	16	41.5
	115(Parallel) Or 230(Series)	VB304S-06006	6	100	10.5	T 70 B	16	41.5
		VB304S-07006	7.2	83	12.6	T 70 B	16	41.5
		VB304S-09006	9	66	15.5	T 70 B	16	41.5
		VB304S-10006	10	60	16	T 70 B	16	41.5
		VB304S-12006	12	50	20.5	T 70 B	16	41.5
		VB304S-15006	15	40	25.4	T 70 B	16	41.5
		VB304S-18006	18	33	30.4	T 70 B	16	41.5
		VB304S-24006	24	25	40.4	T 70 B	16	41.5
		VB304D-06006	6	2x50	2x10.5	T 70 B	16	41.5
		VB304D-07006	7.2	2x42	2x12.6	T 70 B	16	41.5
		VB304D-09006	9	2x33	2x15.5	T 70 B	16	41.5
		VB304D-10006	10	2x30	2x16	T 70 B	16	41.5
		VB304D-12006	12	2x25	2x20.5	T 70 B	16	41.5
		VB304D-15006	15	2x20	2x25.0	T 70 B	16	41.5
		VB304D-18006	18	2x17	2x30.4	T 70 B	16	41.5

ENCAPSULATED TRANSFORMER 密封变压器									
FEATURES			产品特点						
. Frequency 50/60 Hz			. 频率: 50/60 Hz						
. Temperature Class Class B (130° C)			. 温度等级: B级 (130° C)						
. Ambient Temperature (ta) 70° C			. 环境温度: (ta) 70° C						
. Resins Class B IEC86 (20,000H Testing to IEC216)			. 胶温等级: B级 符合IEC86标准 (通过 20,000小时 IEC216标准)						
. Vacuum Potting			. 真空灌胶						
. Flammability Class UL94 V-0			. 材料阻燃等级: UL94 V-0						
. Dielectric Strength 4200Vrms			. 介电强度: 4200Vrms						
. Standard VDE. UL. CUL. CE. CQC			. 标准: VDE. UL. CUL. CE. CQC						
. Conforms EN61558. EN60950. UL1585. UL506			. 符合EN61558. EN60950. UL1585. UL506						
. 200%Tested Production			. 产线200%全检						
OUTLINE DIMENSIONS 外形尺寸			ELECTRICAL SCHEMATIC 电气原理图						
									
EI30-10.5 SERIES 1.0VA									
Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)	
1.0VA	115	VB301S-06010	6	167	8.6	T 70 B	22.3	71.5	
		VB301S-07010	7.2	139	10.3	T 70 B	22.3	71.5	
		VB301S-09010	9	111	12.9	T 70 B	22.3	71.5	
		VB301S-10010	10	100	14.3	T 70 B	22.3	71.5	
		VB301S-12010	12	83	17.2	T 70 B	22.3	71.5	
		VB301S-15010	15	67	21.6	T 70 B	22.3	71.5	
		VB301S-18010	18	56	25.9	T 70 B	22.3	71.5	
		VB301S-24010	24	42	37.9	T 70 B	22.3	71.5	
		VB301D-06010	6	2*83	2*8.6	T 70 B	22.3	71.5	
		VB301D-07010	7.2	2*69	2*10.3	T 70 B	22.3	71.5	
		VB301D-09010	9	2*56	2*12.9	T 70 B	22.3	71.5	
		VB301D-10010	10	2*50	2*14.3	T 70 B	22.3	71.5	
		VB301D-12010	12	2*42	2*19	T 70 B	22.3	71.5	
		VB301D-15010	15	2*33	2*23.6	T 70 B	22.3	71.5	
		VB301D-18010	18	2*28	2*24.9	T 70 B	22.3	71.5	
	230	VB302S-06010	6	167	8.6	T 70 B	22.3	71.5	
		VB302S-07010	7.2	139	10.3	T 70 B	22.3	71.5	
		VB302S-09010	9	111	12.9	T 70 B	22.3	71.5	
		VB302S-10010	10	100	14.3	T 70 B	22.3	71.5	
		VB302S-12010	12	83	17.2	T 70 B	22.3	71.5	
		VB302S-15010	15	67	21.6	T 70 B	22.3	71.5	
		VB302S-18010	18	56	25.9	T 70 B	22.3	71.5	
		VB302S-24010	24	42	37.9	T 70 B	22.3	71.5	
		VB302D-06010	6	2*83	2*8.6	T 70 B	22.3	71.5	
		VB302D-07010	7.2	2*69	2*10.3	T 70 B	22.3	71.5	
		VB302D-09010	9	2*56	2*12.9	T 70 B	22.3	71.5	
		VB302D-10010	10	2*50	2*14.3	T 70 B	22.3	71.5	
		VB302D-12010	12	2*42	2*19	T 70 B	22.3	71.5	
		VB302D-15010	15	2*33	2*23.6	T 70 B	22.3	71.5	
		VB302D-18010	18	2*28	2*24.9	T 70 B	22.3	71.5	
	400	VB303S-06010	6	167	8.6	T 70 B	22.3	71.5	
		VB303S-07010	7.2	139	10.3	T 70 B	22.3	71.5	
		VB303S-09010	9	111	12.9	T 70 B	22.3	71.5	
		VB303S-10010	10	100	14.3	T 70 B	22.3	71.5	
		VB303S-12010	12	83	17.2	T 70 B	22.3	71.5	
		VB303S-15010	15	67	21.6	T 70 B	22.3	71.5	
		VB303S-18010	18	56	25.9	T 70 B	22.3	71.5	
		VB303S-24010	24	42	37.9	T 70 B	22.3	71.5	
		VB303D-06010	6	2*83	2*8.6	T 70 B	22.3	71.5	
		VB303D-07010	7.2	2*69	2*10.3	T 70 B	22.3	71.5	
		VB303D-09010	9	2*56	2*12.9	T 70 B	22.3	71.5	
		VB303D-10010	10	2*50	2*14.3	T 70 B	22.3	71.5	
		VB303D-12010	12	2*42	2*19	T 70 B	22.3	71.5	
		VB303D-15010	15	2*33	2*23.6	T 70 B	22.3	71.5	
		VB303D-18010	18	2*28	2*24.9	T 70 B	22.3	71.5	
	115(Parallel) Or 230(Series)	VB304S-06010	6	167	8.6	T 70 B	22.3	71.5	
		VB304S-07010	7.2	139	10.3	T 70 B	22.3	71.5	
		VB304S-09010	9	111	12.9	T 70 B	22.3	71.5	
		VB304S-10010	10	100	14.3	T 70 B	22.3	71.5	
		VB304S-12010	12	83	17.2	T 70 B	22.3	71.5	
		VB304S-15010	15	67	21.6	T 70 B	22.3	71.5	
		VB304S-18010	18	56	25.9	T 70 B	22.3	71.5	
		VB304S-24010	24	42	37.9	T 70 B	22.3	71.5	
		VB304D-06010	6	2*83	2*8.6	T 70 B	22.3	71.5	
		VB304D-07010	7.2	2*69	2*10.3	T 70 B	22.3	71.5	
		VB304D-09010	9	2*56	2*12.9	T 70 B	22.3	71.5	
		VB304D-10010	10	2*50	2*14.3	T 70 B	22.3	71.5	
		VB304D-12010	12	2*42	2*19	T 70 B	22.3	71.5	
		VB304D-15010	15	2*33	2*23.6	T 70 B	22.3	71.5	
		VB304D-18010	18	2*28	2*24.9	T 70 B	22.3	71.5	

ENCAPSULATED TRANSFORMER 密封变压器


FEATURES

- Frequency 50/60 Hz
- Temperature Class Class B (130° C)
- Ambient Temperature (ta) 70° C
- Resins Class B IEC86 (20,000H Testing to IEC216)
- Vacuum Potting
- Flammability Class UL94 V-0
- Dielectric Strength 4200Vrms
- Standard CE
- Conforms EN61558, EN60950, UL1585, UL506
- 200% Tested Production


产品特点

- 频率: 50/60 Hz
- 温度等级: B级 (130° C)
- 环境温度: (ta) 70° C
- 胶温等级: B级 符合IEC86标准 (通过 20,000小时 IEC216标准)
- 真空灌胶
- 材料阻燃等级: UL94 V-0
- 介电强度: 4200Vrms
- 标准: CE
- 符合EN61558, EN60950, UL1585, UL506
- 产线200%全检

OUTLINE DIMENSIONS 外形尺寸



ELECTRICAL SCHEMATIC 电气原理图




EI30-10.5 SERIES 1.2VA

Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
1.2VA	115	VB301S-06012	6	200	8.6	T 70 B	22.3	71.5
		VB301S-07012	7.2	167	10.3	T 70 B	22.3	71.5
		VB301S-09012	9	133	12.9	T 70 B	22.3	71.5
		VB301S-10012	10	120	14.3	T 70 B	22.3	71.5
		VB301S-12012	12	100	17.2	T 70 B	22.3	71.5
		VB301S-15012	15	80	21.6	T 70 B	22.3	71.5
		VB301S-18012	18	67	25.9	T 70 B	22.3	71.5
		VB301S-24012	24	50	37.9	T 70 B	22.3	71.5
		VB301D-06012	6	2x100	2x8.6	T 70 B	22.3	71.5
		VB301D-07012	7.2	2x83	2x10.3	T 70 B	22.3	71.5
		VB301D-09012	9	2x67	2x12.9	T 70 B	22.3	71.5
		VB301D-10012	10	2x60	2x14.3	T 70 B	22.3	71.5
		VB301D-12012	12	2x50	2x19	T 70 B	22.3	71.5
		VB301D-15012	15	2x40	2x23.6	T 70 B	22.3	71.5
		VB301D-18012	18	2x33	2x24.9	T 70 B	22.3	71.5
	230	VB302S-06012	6	200	8.6	T 70 B	22.3	71.5
		VB302S-07012	7.2	167	10.3	T 70 B	22.3	71.5
		VB302S-09012	9	133	12.9	T 70 B	22.3	71.5
		VB302S-10012	10	120	14.3	T 70 B	22.3	71.5
		VB302S-12012	12	100	17.2	T 70 B	22.3	71.5
		VB302S-15012	15	80	21.6	T 70 B	22.3	71.5
		VB302S-18012	18	67	25.9	T 70 B	22.3	71.5
		VB302S-24012	24	50	37.9	T 70 B	22.3	71.5
		VB302D-06012	6	2x100	2x8.6	T 70 B	22.3	71.5
		VB302D-07012	7.2	2x83	2x10.3	T 70 B	22.3	71.5
		VB302D-09012	9	2x67	2x12.9	T 70 B	22.3	71.5
		VB302D-10012	10	2x60	2x14.3	T 70 B	22.3	71.5
		VB302D-12012	12	2x50	2x19	T 70 B	22.3	71.5
		VB302D-15012	15	2x40	2x23.6	T 70 B	22.3	71.5
		VB302D-18012	18	2x33	2x24.9	T 70 B	22.3	71.5
	400	VB303S-06012	6	200	8.6	T 70 B	22.3	71.5
		VB303S-07012	7.2	167	10.3	T 70 B	22.3	71.5
		VB303S-09012	9	133	12.9	T 70 B	22.3	71.5
		VB303S-10012	10	120	14.3	T 70 B	22.3	71.5
		VB303S-12012	12	100	17.2	T 70 B	22.3	71.5
		VB303S-15012	15	80	21.6	T 70 B	22.3	71.5
		VB303S-18012	18	67	25.9	T 70 B	22.3	71.5
		VB303S-24012	24	50	37.9	T 70 B	22.3	71.5
		VB303D-06012	6	2x100	2x8.6	T 70 B	22.3	71.5
		VB303D-07012	7.2	2x83	2x10.3	T 70 B	22.3	71.5
		VB303D-09012	9	2x67	2x12.9	T 70 B	22.3	71.5
		VB303D-10012	10	2x60	2x14.3	T 70 B	22.3	71.5
		VB303D-12012	12	2x50	2x19	T 70 B	22.3	71.5
		VB303D-15012	15	2x40	2x23.6	T 70 B	22.3	71.5
		VB303D-18012	18	2x33	2x24.9	T 70 B	22.3	71.5
	115(Parallel) Or 230(Series)	VB304S-06012	6	200	8.6	T 70 B	22.3	71.5
		VB304S-07012	7.2	167	10.3	T 70 B	22.3	71.5
		VB304S-09012	9	133	12.9	T 70 B	22.3	71.5
		VB304S-10012	10	120	14.3	T 70 B	22.3	71.5
		VB304S-12012	12	100	17.2	T 70 B	22.3	71.5
		VB304S-15012	15	80	21.6	T 70 B	22.3	71.5
		VB304S-18012	18	67	25.9	T 70 B	22.3	71.5
		VB304S-24012	24	50	37.9	T 70 B	22.3	71.5
		VB304D-06012	6	2x100	2x8.6	T 70 B	22.3	71.5
		VB304D-07012	7.2	2x83	2x10.3	T 70 B	22.3	71.5
		VB304D-09012	9	2x67	2x12.9	T 70 B	22.3	71.5
		VB304D-10012	10	2x60	2x14.3	T 70 B	22.3	71.5
		VB304D-12012	12	2x50	2x19	T 70 B	22.3	71.5
		VB304D-15012	15	2x40	2x23.6	T 70 B	22.3	71.5
		VB304D-18012	18	2x33	2x24.9	T 70 B	22.3	71.5

产品特点

- ELECTRICAL SCHEMATIC 电气原理图



Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-Load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
115		VB301S-06015A	6	250	10.1	T 40 B	22.3	71.5
		VB301S-07015A	7.2	208	12.3	T 40 B	22.3	71.5
		VB301S-09015A	9	167	15.3	T 40 B	22.3	71.5
		VB301S-10015A	10	150	17	T 40 B	22.3	71.5
		VB301S-12015A	12	125	20.2	T 40 B	22.3	71.5
		VB301S-15015A	15	100	25.3	T 40 B	22.3	71.5
		VB301S-18015A	18	83	31.2	T 40 B	22.3	71.5
		VB301S-24015A	24	63	43.3	T 40 B	22.3	71.5
		VB301D-06015A	6	2x125	2x10.1	T 40 B	22.3	71.5
		VB301D-07015A	7.2	2x104	2x12.3	T 40 B	22.3	71.5
		VB301D-09015A	9	2x83	2x15.3	T 40 B	22.3	71.5
		VB301D-10015A	10	2x75	2x17	T 40 B	22.3	71.5
		VB301D-12015A	12	2x63	2x20.2	T 40 B	22.3	71.5
		VB301D-15015A	15	2x50	2x25.0	T 40 B	22.3	71.5
		VB301D-18015A	18	2x42	2x31	T 40 B	22.3	71.5
		VB302S-06015A	6	250	10.1	T 40 B	22.3	71.5
		VB302S-07015A	7.2	208	12.3	T 40 B	22.3	71.5
		VB302S-09015A	9	167	15.3	T 40 B	22.3	71.5
		VB302S-10015A	10	150	17	T 40 B	22.3	71.5
		VB302S-12015A	12	125	20.2	T 40 B	22.3	71.5
		VB302S-15015A	15	100	25.3	T 40 B	22.3	71.5
		VB302S-18015A	18	83	31.2	T 40 B	22.3	71.5
		VB302S-24015A	24	63	43.3	T 40 B	22.3	71.5
			VB302D-06015A	6	2x125	2x10.1	T 40 B	22.3
VB302D-07015A	7.2		2x104	2x12.3	T 40 B	22.3	71.5	
VB302D-09015A	9		2x83	2x15.3	T 40 B	22.3	71.5	
VB302D-10015A	10		2x75	2x17	T 40 B	22.3	71.5	
VB302D-12015A	12		2x63	2x20.2	T 40 B	22.3	71.5	
VB302D-15015A	15		2x50	2x25.0	T 40 B	22.3	71.5	
VB302D-18015A	18		2x42	2x31	T 40 B	22.3	71.5	
VB303S-06015A	6		250	10.1	T 40 B	22.3	71.5	
VB303S-07015A	7.2		208	12.3	T 40 B	22.3	71.5	
VB303S-09015A	9		167	15.3	T 40 B	22.3	71.5	
VB303S-10015A	10		150	17	T 40 B	22.3	71.5	
400			VB303S-12015A	12	125	20.2	T 40 B	22.3
		VB303S-15015A	15	100	25.3	T 40 B	22.3	71.5
		VB303S-18015A	18	83	31.2	T 40 B	22.3	71.5
		VB303S-24015A	24	63	43.3	T 40 B	22.3	71.5
		VB303D-06015A	6	2x125	2x10.1	T 40 B	22.3	71.5
		VB303D-07015A	7.2	2x104	2x12.3	T 40 B	22.3	71.5
		VB303D-09015A	9	2x83	2x15.3	T 40 B	22.3	71.5
		VB303D-10015A	10	2x75	2x17	T 40 B	22.3	71.5
		VB303D-12015A	12	2x63	2x20.2	T 40 B	22.3	71.5
		VB303D-15015A	15	2x50	2x25.0	T 40 B	22.3	71.5
		VB303D-18015A	18	2x42	2x31	T 40 B	22.3	71.5
			VB304S-06015A	6	250	10.1	T 40 B	22.3
	VB304S-07015A		7.2	208	12.3	T 40 B	22.3	71.5
	VB304S-09015A		9	167	15.3	T 40 B	22.3	71.5
	VB304S-10015A		10	150	17	T 40 B	22.3	71.5
	VB304S-12015A		12	125	20.2	T 40 B	22.3	71.5
	VB304S-15015A		15	100	25.3	T 40 B	22.3	71.5
	VB304S-18015A		18	83	31.2	T 40 B	22.3	71.5
	VB304S-24015A		24	63	43.3	T 40 B	22.3	71.5
	VB304D-06015A		6	2x125	2x10.1	T 40 B	22.3	71.5
	VB304D-07015A		7.2	2x104	2x12.3	T 40 B	22.3	71.5
	VB304D-09015A		9	2x83	2x15.3	T 40 B	22.3	71.5
	VB304D-10015A		10	2x75	2x17	T 40 B	22.3	71.5
		VB304D-12015A	12	2x63	2x20.2	T 40 B	22.3	71.5
VB304D-15015A		15	2x50	2x25.0	T 40 B	22.3	71.5	
VB304D-18015A		18	2x42	2x31	T 40 B	22.3	71.5	
115(Parallel) Or 230(Series)		VB304S-06015A	6	250	10.1	T 40 B	22.3	71.5
		VB304S-07015A	7.2	208	12.3	T 40 B	22.3	71.5
		VB304S-09015A	9	167	15.3	T 40 B	22.3	71.5
		VB304S-10015A	10	150	17	T 40 B	22.3	71.5
		VB304S-12015A	12	125	20.2	T 40 B	22.3	71.5
		VB304S-15015A	15	100	25.3	T 40 B	22.3	71.5
		VB304S-18015A	18	83	31.2	T 40 B	22.3	71.5
		VB304S-24015A	24	63	43.3	T 40 B	22.3	71.5

ENCAPSULATED TRANSFORMER 密封变压器


FEATURES

- Frequency 50/60 Hz
- Temperature Class Class B (130° C)
- Ambient Temperature (ta) 70° C
- Resins Class B IEC86 (20,000H Testing to IEC216)
- Vacuum Potting
- Flammability Class UL94 V-0
- Dielectric Strength 4200Vrms
- Standard VDE. UL. CUL. CE. CQC
- Conforms EN61558. EN60950. UL1585. UL506
- 200%Tested Production


产品特点

- 频率: 50/60 Hz
- 温度等级: B级 (130° C)
- 环境温度: (ta) 70° C
- 胶温等级: B级 符合IEC86标准 (通过 20,000小时 IEC216标准)
- 真空灌胶
- 材料阻燃等级: UL94 V-0
- 介电强度: 4200Vrms
- 标准: VDE. UL. CUL. CE. CQC
- 符合EN61558. EN60950. UL1585. UL506
- 产线200%全检

OUTLINE DIMENSIONS 外形尺寸



ELECTRICAL SCHEMATIC 电气原理图



EI30-12.5 SERIES 1.5VA

Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)	
1.5VA	115	VB301S-0601S	6	250	9.7	T 70 B	24.4	82	
		VB301S-0701S	7.2	208	11.2	T 70 B	24.4	82	
		VB301S-0901S	9	167	14.5	T 70 B	24.4	82	
		VB301S-1001S	10	150	15.5	T 70 B	24.4	82	
		VB301S-1201S	12	125	19.3	T 70 B	24.4	82	
		VB301S-1501S	15	100	24.2	T 70 B	24.4	82	
		VB301S-1801S	18	83	29.8	T 70 B	24.4	82	
		VB301S-2401S	24	63	38.6	T 70 B	24.4	82	
		VB301D-0601S	6	2x125	2x9.7	T 70 B	24.4	82	
		VB301D-0701S	7	2x104	2x11.2	T 70 B	24.4	82	
		VB301D-0901S	9	2x83	2x14.5	T 70 B	24.4	82	
		VB301D-1001S	10	2x75	2x15.5	T 70 B	24.4	82	
		VB301D-1201S	12	2x63	2x19.3	T 70 B	24.4	82	
		VB301D-1501S	15	2x50	2x24.2	T 70 B	24.4	82	
		VB301D-1801S	18	2x42	2x29	T 70 B	24.4	82	
	230	VB302S-0601S	6	250	9.7	T 70 B	24.4	82	
		VB302S-0701S	7.2	208	11.2	T 70 B	24.4	82	
		VB302S-0901S	9	167	14.5	T 70 B	24.4	82	
		VB302S-1001S	10	150	15.5	T 70 B	24.4	82	
		VB302S-1201S	12	125	19.3	T 70 B	24.4	82	
		VB302S-1501S	15	100	24.2	T 70 B	24.4	82	
		VB302S-1801S	18	83	29.8	T 70 B	24.4	82	
		VB302S-2401S	24	63	38.6	T 70 B	24.4	82	
		VB302D-0601S	6	2x125	2x9.7	T 70 B	24.4	82	
		VB302D-0701S	7.2	2x104	2x11.2	T 70 B	24.4	82	
		VB302D-0901S	9	2x83	2x14.5	T 70 B	24.4	82	
		VB302D-1001S	10	2x75	2x15.5	T 70 B	24.4	82	
		400	VB303S-0601S	6	250	9.7	T 70 B	24.4	82
			VB303S-0701S	7.2	208	11.2	T 70 B	24.4	82
			VB303S-0901S	9	167	14.5	T 70 B	24.4	82
	VB303S-1001S		10	150	15.5	T 70 B	24.4	82	
	VB303S-1201S		12	125	19.3	T 70 B	24.4	82	
	VB303S-1501S		15	100	24.2	T 70 B	24.4	82	
	VB303S-1801S		18	83	29.8	T 70 B	24.4	82	
	VB303S-2401S		24	63	38.6	T 70 B	24.4	82	
	VB303D-0601S		6	2x125	2x9.7	T 70 B	24.4	82	
	VB303D-0701S		7.2	2x104	2x11.2	T 70 B	24.4	82	
	VB303D-0901S		9	2x83	2x15	T 70 B	24.4	82	
	VB303D-1001S		10	2x75	2x15.5	T 70 B	24.4	82	
	115(Parallel) Or 230(Series)	VB303D-1201S	12	2x63	2x19.3	T 70 B	24.4	82	
		VB303D-1501S	15	2x50	2x24.2	T 70 B	24.4	82	
		VB303D-1801S	18	2x42	2x29	T 70 B	24.4	82	
VB304S-0601S		6	250	9.7	T 70 B	24.4	82		
VB304S-0701S		7.2	208	11.2	T 70 B	24.4	82		
VB304S-0901S		9	167	14.5	T 70 B	24.4	82		
VB304S-1001S		10	150	15.5	T 70 B	24.4	82		
VB304S-1201S		12	125	19.3	T 70 B	24.4	82		
VB304S-1501S		15	100	24.2	T 70 B	24.4	82		
VB304S-1801S		18	83	29.8	T 70 B	24.4	82		
VB304S-2401S		24	63	38.6	T 70 B	24.4	82		
VB304D-0601S		6	2x125	2x9.7	T 70 B	24.4	82		
VB304D-0701S		7.2	2x104	2x11.2	T 70 B	24.4	82		
VB304D-0901S		9	2x83	2x14.5	T 70 B	24.4	82		
VB304D-1001S		10	2x75	2x15.5	T 70 B	24.4	82		
VB304D-1201S	12	2x63	2x19.3	T 70 B	24.4	82			
VB304D-1501S	15	2x50	2x24.2	T 70 B	24.4	82			
VB304D-1801S	18	2x42	2x29	T 70 B	24.4	82			

产品特点

- ELECTRICAL SCHEMATIC 电气原理图



Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
1.8VA	115	VB301S-06018	6	300	9.8	T 40 B	24.4	82
		VB301S-07018	7.2	250	12.3	T 40 B	24.4	82
		VB301S-09018	9	200	14.8	T 40 B	24.4	82
		VB301S-10018	10	180	15.2	T 40 B	24.4	82
		VB301S-12018	12	150	19.7	T 40 B	24.4	82
		VB301S-15018	15	120	24.6	T 40 B	24.4	82
		VB301S-18018	18	100	30.3	T 40 B	24.4	82
		VB301S-24018	24	75	39.3	T 40 B	24.4	82
		VB301D-06018	6	2×150	2×9.8	T 40 B	24.4	82
		VB301D-07018	7.2	2×125	2×12.3	T 40 B	24.4	82
		VB301D-09018	9	2×100	2×15.2	T 40 B	24.4	82
		VB301D-10018	10	2×90	2×15.6	T 40 B	24.4	82
		VB301D-12018	12	2×75	2×19.7	T 40 B	24.4	82
		VB301D-15018	15	2×60	2×24.6	T 40 B	24.4	82
		VB301D-18018	18	2×50	2×29.5	T 40 B	24.4	82
		VB302S-06018	6	300	9.8	T 40 B	24.4	82
		VB302S-07018	7.2	250	12.3	T 40 B	24.4	82
		VB302S-09018	9	200	14.8	T 40 B	24.4	82
230	VB302S-10018	10	180	15.2	T 40 B	24.4	82	
	VB302S-12018	12	150	19.7	T 40 B	24.4	82	
	VB302S-15018	15	120	24.6	T 40 B	24.4	82	
	VB302S-18018	18	100	30.3	T 40 B	24.4	82	
	VB302S-24018	24	75	39.3	T 40 B	24.4	82	
	VB302D-06018	6	2×150	2×9.8	T 40 B	24.4	82	
	VB302D-07018	7.2	2×125	2×12.3	T 40 B	24.4	82	
	VB302D-09018	9	2×100	2×15.2	T 40 B	24.4	82	
	VB302D-10018	10	2×90	2×15.6	T 40 B	24.4	82	
	VB302D-12018	12	2×75	2×19.7	T 40 B	24.4	82	
	VB302D-15018	15	2×60	2×24.6	T 40 B	24.4	82	
	VB303S-06018	6	300	9.8	T 40 B	24.4	82	
	VB303S-07018	7.2	250	12.3	T 40 B	24.4	82	
	VB303S-09018	9	200	14.8	T 40 B	24.4	82	
	VB303S-10018	10	180	15.2	T 40 B	24.4	82	
	VB303S-12018	12	150	19.7	T 40 B	24.4	82	
	VB303S-15018	15	120	24.6	T 40 B	24.4	82	
	VB303S-18018	18	100	30.3	T 40 B	24.4	82	
400	VB303S-24018	24	75	39.3	T 40 B	24.4	82	
	VB303D-06018	6	2×150	2×9.8	T 40 B	24.4	82	
	VB303D-07018	7.2	2×125	2×12.3	T 40 B	24.4	82	
	VB303D-09018	9	2×100	2×15.2	T 40 B	24.4	82	
	VB303D-10018	10	2×90	2×15.6	T 40 B	24.4	82	
	VB303D-12018	12	2×75	2×19.7	T 40 B	24.4	82	
	VB303D-15018	15	2×60	2×24.6	T 40 B	24.4	82	
	VB303D-18018	18	2×50	2×29.5	T 40 B	24.4	82	
	VB304S-06018	6	300	9.8	T 40 B	24.4	82	
	VB304S-07018	7.2	250	12.3	T 40 B	24.4	82	
	VB304S-09018	9	200	14.8	T 40 B	24.4	82	
	VB304S-10018	10	180	15.2	T 40 B	24.4	82	
	VB304S-12018	12	150	19.7	T 40 B	24.4	82	
	VB304S-15018	15	120	24.6	T 40 B	24.4	82	
	VB304S-18018	18	100	30.3	T 40 B	24.4	82	
	VB304S-24018	24	75	39.3	T 40 B	24.4	82	
	115(Parallel) Or 230(Series)	VB304D-06018	6	2×150	2×9.8	T 40 B	24.4	82
		VB304D-07018	7.2	2×125	2×12.3	T 40 B	24.4	82
VB304D-09018		9	2×100	2×15.2	T 40 B	24.4	82	
VB304D-10018		10	2×90	2×15.6	T 40 B	24.4	82	
VB304D-12018		12	2×75	2×19.7	T 40 B	24.4	82	
VB304D-15018		15	2×60	2×24.6	T 40 B	24.4	82	
VB304D-18018		18	2×50	2×29.5	T 40 B	24.4	82	

ENCAPSULATED TRANSFORMER 密封变压器


FEATURES

- Frequency 50/60 Hz
- Temperature Class Class B (130° C)
- Ambient Temperature (ta) 70° C
- Resins Class B IEC86 (20,000H Testing to IEC216)
- Vacuum Potting
- Flammability Class UL94 V-0
- Dielectric Strength 4200Vrms
- Standard VDE. UL. CUL. CE. CQC
- Conforms EN61558. EN60950. UL1585. UL506
- 200%Tested Production


产品特点

- 频率: 50/60 Hz
- 温度等级: B级 (130° C)
- 环境温度: (ta) 70° C
- 胶温度等级: B级 符合IEC86标准 (通过 20,000小时 IEC216标准)
- 真空灌胶
- 材料阻燃等级: UL94 V-0
- 介电强度: 4200Vrms
- 标准: VDE. UL. CUL. CE. CQC
- 符合EN61558. EN60950. UL1585. UL506
- 产线200%全检

OUTLINE DIMENSIONS 外形尺寸



ELECTRICAL SCHEMATIC 电气原理图



EI30-16.5 SERIES 2.0VA								
Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
2.0VA	115	VB301S-06020	6	333	10.4	T 70 B	27.4	100
		VB301S-07020	7.2	278	12.6	T 70 B	27.4	100
		VB301S-09020	9	222	15.5	T 70 B	27.4	100
		VB301S-10020	10	200	16	T 70 B	27.4	100
		VB301S-12020	12	167	20.7	T 70 B	27.4	100
		VB301S-15020	15	133	25.8	T 70 B	27.4	100
		VB301S-18020	18	111	30.8	T 70 B	27.4	100
		VB301S-24020	24	83	41.4	T 70 B	27.4	100
		VB301D-06020	6	2x167	2x10.4	T 70 B	27.4	100
		VB301D-07020	7.2	2x139	2x12.6	T 70 B	27.4	100
		VB301D-09020	9	2x111	2x15.5	T 70 B	27.4	100
		VB301D-10020	10	2x100	2x16	T 70 B	27.4	100
		VB301D-12020	12	2x83	2x20.7	T 70 B	27.4	100
		VB301D-15020	15	2x67	2x25.0	T 70 B	27.4	100
		VB301D-18020	18	2x56	2x30.8	T 70 B	27.4	100
	230	VB302S-06020	6	333	10.4	T 70 B	27.4	100
		VB302S-07020	7.2	278	12.6	T 70 B	27.4	100
		VB302S-09020	9	222	15.5	T 70 B	27.4	100
		VB302S-10020	10	200	16	T 70 B	27.4	100
		VB302S-12020	12	167	20.7	T 70 B	27.4	100
		VB302S-15020	15	133	25.8	T 70 B	27.4	100
		VB302S-18020	18	111	30.8	T 70 B	27.4	100
		VB302S-24020	24	83	41.4	T 70 B	27.4	100
		VB302D-06020	6	2x167	2x10.4	T 70 B	27.4	100
		VB302D-07020	7.2	2x139	2x12.6	T 70 B	27.4	100
		VB302D-09020	9	2x111	2x15.4	T 70 B	27.4	100
		VB302D-10020	10	2x100	2x16	T 70 B	27.4	100
		VB302D-12020	12	2x83	2x20.7	T 70 B	27.4	100
		VB302D-15020	15	2x67	2x25.0	T 70 B	27.4	100
		VB302D-18020	18	2x56	2x30.8	T 70 B	27.4	100
	400	VB303S-06020	6	333	10.4	T 70 B	27.4	100
		VB303S-07020	7.2	278	12.6	T 70 B	27.4	100
		VB303S-09020	9	222	15.5	T 70 B	27.4	100
		VB303S-10020	10	200	16	T 70 B	27.4	100
		VB303S-12020	12	167	20.7	T 70 B	27.4	100
		VB303S-15020	15	133	25.8	T 70 B	27.4	100
		VB303S-18020	18	111	30.8	T 70 B	27.4	100
		VB303S-24020	24	83	41.4	T 70 B	27.4	100
		VB303D-06020	6	2x167	2x10.4	T 70 B	27.4	100
		VB303D-07020	7.2	2x139	2x12.6	T 70 B	27.4	100
		VB303D-09020	9	2x111	2x15.4	T 70 B	27.4	100
		VB303D-10020	10	2x100	2x16	T 70 B	27.4	100
		VB303D-12020	12	2x83	2x20.7	T 70 B	27.4	100
		VB303D-15020	15	2x67	2x25.0	T 70 B	27.4	100
		VB303D-18020	18	2x56	2x30.8	T 70 B	27.4	100
	115(Parallel) Or 230(Series)	VB304S-06020	6	333	10.4	T 70 B	27.4	100
		VB304S-07020	7.2	278	12.6	T 70 B	27.4	100
		VB304S-09020	9	222	15.5	T 70 B	27.4	100
		VB304S-10020	10	200	16	T 70 B	27.4	100
		VB304S-12020	12	167	20.7	T 70 B	27.4	100
		VB304S-15020	15	133	25.8	T 70 B	27.4	100
		VB304S-18020	18	111	30.8	T 70 B	27.4	100
		VB304S-24020	24	83	41.4	T 70 B	27.4	100
		VB304D-06020	6	2x167	2x10.4	T 70 B	27.4	100
		VB304D-07020	7.2	2x139	2x12.6	T 70 B	27.4	100
		VB304D-09020	9	2x111	2x15.4	T 70 B	27.4	100
		VB304D-10020	10	2x100	2x16	T 70 B	27.4	100
		VB304D-12020	12	2x83	2x20.7	T 70 B	27.4	100
		VB304D-15020	15	2x67	2x25.0	T 70 B	27.4	100
		VB304D-18020	18	2x56	2x30.8	T 70 B	27.4	100

ENCAPSULATED TRANSFORMER 密封变压器


FEATURES

- Frequency 50/60 Hz
- Temperature Class Class B (130° C)
- Ambient Temperature (ta) 60° C
- Resins Class B IEC85 (20,000H Testing to IEC216)
- Vacuum Potting
- Flammability Class UL94 V-0
- Dielectric Strength 4200Vrms
- Standard VDE. UL. CUL. CE. CQC
- Conforms EN61558. EN60950. UL1585. UL506
- 200%Tested Production


产品特点

- 频率: 50/60 Hz
- 温度等级: B级 (130° C)
- 环境温度: (ta) 60° C
- 胶温等级: B级 符合IEC85标准 (通过 20,000小时 IEC216标准)
- 真空灌胶
- 材料阻燃等级: UL94 V-0
- 介电强度: 4200Vrms
- 标准: VDE. UL. CUL. CE. CQC
- 符合EN61558. EN60950. UL1585. UL506
- 产线200%全检

OUTLINE DIMENSIONS 外形尺寸







ELECTRICAL SCHEMATIC 电气原理图



EI30-18 SERIES 2.3VA

Product Series	Primary Voltage (V)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
2.3VA	115	VB301S-06023	6	383	10.5	T 60 B	29.8	110
		VB301S-07023	7.2	319	13.2	T 60 B	29.8	110
		VB301S-09023	9	256	15.7	T 60 B	29.8	110
		VB301S-10023	10	230	16	T 60 B	29.8	110
		VB301S-12023	12	192	21	T 60 B	29.8	110
		VB301S-15023	15	153	25.9	T 60 B	29.8	110
		VB301S-18023	18	128	31.4	T 60 B	29.8	110
		VB301S-24023	24	96	41.9	T 60 B	29.8	110
		VB301D-06023	6	2x192	2x10.5	T 60 B	29.8	110
		VB301D-07023	7.2	2x160	2x13.2	T 60 B	29.8	110
		VB301D-09023	9	2x128	2x15.5	T 60 B	29.8	110
		VB301D-10023	10	2x115	2x16	T 60 B	29.8	110
		VB301D-12023	12	2x96	2x21	T 60 B	29.8	110
		VB301D-15023	15	2x77	2x25.0	T 60 B	29.8	110
		VB301D-18023	18	2x64	2x31.4	T 60 B	29.8	110
	230	VB302S-06023	6	383	10.5	T 60 B	29.8	110
		VB302S-07023	7.2	319	13.2	T 60 B	29.8	110
		VB302S-09023	9	256	15.7	T 60 B	29.8	110
		VB302S-10023	10	230	16	T 60 B	29.8	110
		VB302S-12023	12	192	21	T 60 B	29.8	110
		VB302S-15023	15	153	25.9	T 60 B	29.8	110
		VB302S-18023	18	128	31.4	T 60 B	29.8	110
		VB302S-24023	24	96	41.9	T 60 B	29.8	110
		VB302D-06023	6	2x192	2x10.5	T 60 B	29.8	110
		VB302D-07023	7.2	2x160	2x13.2	T 60 B	29.8	110
		VB302D-09023	9	2x128	2x15.5	T 60 B	29.8	110
		VB302D-10023	10	2x115	2x16	T 60 B	29.8	110
		VB302D-12023	12	2x96	2x21	T 60 B	29.8	110
		VB302D-15023	15	2x77	2x25.0	T 60 B	29.8	110
		VB302D-18023	18	2x64	2x31.4	T 60 B	29.8	110
	400	VB303S-06023	6	383	10.5	T 60 B	29.8	110
		VB303S-07023	7.2	319	13.2	T 60 B	29.8	110
		VB303S-09023	9	256	15.7	T 60 B	29.8	110
		VB303S-10023	10	230	16	T 60 B	29.8	110
		VB303S-12023	12	192	21	T 60 B	29.8	110
		VB303S-15023	15	153	25.9	T 60 B	29.8	110
		VB303S-18023	18	128	31.4	T 60 B	29.8	110
		VB303S-24023	24	96	41.9	T 60 B	29.8	110
		VB303D-06023	6	2x192	2x10.5	T 60 B	29.8	110
		VB303D-07023	7.2	2x160	2x13.2	T 60 B	29.8	110
		VB303D-09023	9	2x128	2x15.5	T 60 B	29.8	110
		VB303D-10023	10	2x115	2x16	T 60 B	29.8	110
		VB303D-12023	12	2x96	2x21	T 60 B	29.8	110
		VB303D-15023	15	2x77	2x25.0	T 60 B	29.8	110
		VB303D-18023	18	2x64	2x31.4	T 60 B	29.8	110
	115(Parallel) Or 230(Series)	VB304S-06023	6	383	10.5	T 60 B	29.8	110
		VB304S-07023	7.2	319	13.2	T 60 B	29.8	110
		VB304S-09023	9	256	15.7	T 60 B	29.8	110
		VB304S-10023	10	230	16	T 60 B	29.8	110
		VB304S-12023	12	192	21	T 60 B	29.8	110
		VB304S-15023	15	153	25.9	T 60 B	29.8	110
		VB304S-18023	18	128	31.4	T 60 B	29.8	110
		VB304S-24023	24	96	41.9	T 60 B	29.8	110
		VB304D-06023	6	2x192	2x10.5	T 60 B	29.8	110
		VB304D-07023	7.2	2x160	2x13.2	T 60 B	29.8	110
		VB304D-09023	9	2x128	2x15.5	T 60 B	29.8	110
		VB304D-10023	10	2x115	2x16	T 60 B	29.8	110
		VB304D-12023	12	2x96	2x21	T 60 B	29.8	110
		VB304D-15023	15	2x77	2x25.0	T 60 B	29.8	110
		VB304D-18023	18	2x64	2x31.4	T 60 B	29.8	110

ENCAPSULATED TRANSFORMER 密封变压器											
FEATURES					产品特点						
. Frequency 50/60 Hz					. 频率: 50/60 Hz						
. Temperature Class Class B (130° C)					. 温度等级: B级 (130° C)						
. Ambient Temperature (ta) 70° C					. 环境温度: (ta) 70° C						
. Resins Class B IEC85 (20,000H Testing to IEC216)					. 胶温度等级: B级 附合IEC85标准 (通过 20,000小时 IEC216标准)						
. Vacuum Potting					. 真空灌胶						
. Flammability Class UL94 V-0					. 材料阻燃等级: UL94 V-0						
. Dielectric Strength 4200Vrms					. 介电强度: 4200Vrms						
. Standard CE,CQC					. 标准: CE ,CQC						
. Conforms EN61558, EN60950, UL1585, UL506					. 符合EN61558, EN60950, UL1585, UL506						
. 200%Tested Production					. 产线200%全检						
OUTLINE DIMENSIONS 外形尺寸					ELECTRICAL SCHEMATIC 电气原理图						
											
EI38-13.6 SERIES 3.2VA											
Product Series	Primary Voltage (V)	Secondary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)		
115	630		VB381S-06032	6	534	8.9	T 70 B	28.3	153		
	400		VB381S-07032	7.2	444	10.7	T 70 B	28.3	153		
	315		VB381S-09032	9	356	13	T 70 B	28.3	153		
	315		VB381S-10032	10	320	14.8	T 70 B	28.3	153		
	315		VB381S-12032	12	267	17	T 70 B	28.3	153		
	250		VB381S-15032	15	214	21	T 70 B	28.3	153		
	200		VB381S-18032	18	178	25	T 70 B	28.3	153		
	160		VB381S-24032	24	133	33.5	T 70 B	28.3	153		
	315		VB381D-06032	6	2*267	2*8.9	T 70 B	28.3	153		
	250		VB381D-07032	7.2	2*222	2*10.7	T 70 B	28.3	153		
	200		VB381D-09032	9	2*178	2*13	T 70 B	28.3	153		
	160		VB381D-10032	10	2*160	2*14.8	T 70 B	28.3	153		
	160		VB381D-12032	12	2*134	2*17	T 70 B	28.3	153		
	125		VB381D-15032	15	2*107	2*21	T 70 B	28.3	153		
	100		VB381D-18032	18	2*89	2*25	T 70 B	28.3	153		
	230	630		VB382S-06032	6	534	8.9	T 70 B	28.3	153	
		400		VB382S-07032	7.2	444	10.7	T 70 B	28.3	153	
		315		VB382S-09032	9	356	13	T 70 B	28.3	153	
		315		VB382S-10032	10	320	14.8	T 70 B	28.3	153	
		315		VB382S-12032	12	267	17	T 70 B	28.3	153	
		250		VB382S-15032	15	214	21	T 70 B	28.3	153	
		200		VB382S-18032	18	178	25	T 70 B	28.3	153	
		160		VB382S-24032	24	133	33.5	T 70 B	28.3	153	
		315		VB382D-06032	6	2*267	2*8.9	T 70 B	28.3	153	
250			VB382D-07032	7.2	2*222	2*10.7	T 70 B	28.3	153		
200			VB382D-09032	9	2*178	2*13	T 70 B	28.3	153		
160			VB382D-10032	10	2*160	2*14.8	T 70 B	28.3	153		
3.2VA	630		VB383S-06032	6	534	8.9	T 70 B	28.3	153		
	400		VB383S-07032	7.2	444	10.7	T 70 B	28.3	153		
	315		VB383S-09032	9	356	13	T 70 B	28.3	153		
	315		VB383S-10032	10	320	14.8	T 70 B	28.3	153		
	315		VB383S-12032	12	267	17	T 70 B	28.3	153		
	250		VB383S-15032	15	214	21	T 70 B	28.3	153		
	200		VB383S-18032	18	178	25	T 70 B	28.3	153		
	160		VB383S-24032	24	133	33.5	T 70 B	28.3	153		
	315		VB383D-06032	6	2*267	2*8.9	T 70 B	28.3	153		
	250		VB383D-07032	7.2	2*222	2*10.7	T 70 B	28.3	153		
	200		VB383D-09032	9	2*178	2*13	T 70 B	28.3	153		
	160		VB383D-10032	10	2*160	2*14.8	T 70 B	28.3	153		
	160		VB383D-12032	12	2*134	2*17	T 70 B	28.3	153		
	125		VB383D-15032	15	2*107	2*21	T 70 B	28.3	153		
	100		VB383D-18032	18	2*89	2*25	T 70 B	28.3	153		
400	630		VB384S-06032	6	534	8.9	T 70 B	28.3	153		
	400		VB384S-07032	7.2	444	10.7	T 70 B	28.3	153		
	315		VB384S-09032	9	356	13	T 70 B	28.3	153		
	315		VB384S-10032	10	320	14.8	T 70 B	28.3	153		
	315		VB384S-12032	12	267	17	T 70 B	28.3	153		
	250		VB384S-15032	15	214	21	T 70 B	28.3	153		
	200		VB384S-18032	18	178	25	T 70 B	28.3	153		
	160		VB384S-24032	24	133	33.5	T 70 B	28.3	153		
	315		VB384D-06032	6	2*267	2*8.9	T 70 B	28.3	153		
	250		VB384D-07032	7.2	2*222	2*10.7	T 70 B	28.3	153		
	200		VB384D-09032	9	2*178	2*13	T 70 B	28.3	153		
	160		VB384D-10032	10	2*160	2*14.8	T 70 B	28.3	153		
	160		VB384D-12032	12	2*134	2*17	T 70 B	28.3	153		
	125		VB384D-15032	15	2*107	2*21	T 70 B	28.3	153		
	100		VB384D-18032	18	2*89	2*25	T 70 B	28.3	153		
115 (Parallel) Or 230 (Series)	630		VB384S-06032	6	534	8.9	T 70 B	28.3	153		
	400		VB384S-07032	7.2	444	10.7	T 70 B	28.3	153		
	315		VB384S-09032	9	356	13	T 70 B	28.3	153		
	315		VB384S-10032	10	320	14.8	T 70 B	28.3	153		
	315		VB384S-12032	12	267	17	T 70 B	28.3	153		
	250		VB384S-15032	15	214	21	T 70 B	28.3	153		
	200		VB384S-18032	18	178	25	T 70 B	28.3	153		
	160		VB384S-24032	24	133	33.5	T 70 B	28.3	153		
	315		VB384D-06032	6	2*267	2*8.9	T 70 B	28.3	153		
	250		VB384D-07032	7.2	2*222	2*10.7	T 70 B	28.3	153		
	200		VB384D-09032	9	2*178	2*13	T 70 B	28.3	153		
	160		VB384D-10032	10	2*160	2*14.8	T 70 B	28.3	153		
	160		VB384D-12032	12	2*134	2*17	T 70 B	28.3	153		
	125		VB384D-15032	15	2*107	2*21	T 70 B	28.3	153		
	100		VB384D-18032	18	2*89	2*25	T 70 B	28.3	153		

ENCAPSULATED TRANSFORMER 密封变压器											
FEATURES				产品特点							
. Frequency 50/60 Hz				. 频率: 50/60 Hz							
. Temperature Class Class B (130° C)				. 温度等级: B级 (130° C)							
. Ambient Temperature (ta) 70° C				. 环境温度: (ta) 70° C							
. Resins Class B IEC85 (20,000H Testing to IEC216)				. 胶温度等级: B级 符合IEC85标准 (通过 20,000小时 IEC216标准)							
. Vacuum Potting				. 真空灌胶							
. Flammability Class UL94 V-0				. 材料阻燃等级: UL94 V-0							
. Dielectric Strength 4200Vrms				. 介电强度: 4200Vrms							
. Standard CE,CQC				. 标准: CE,CQC							
. Conforms EN61558, EN60950, UL1585, UL506				. 符合EN61558, EN60950, UL1585, UL506							
. 200%Tested Production				. 产线200%全检							
OUTLINE DIMENSIONS 外形尺寸				ELECTRICAL SCHEMATIC 电气原理图							
											
EI38-13.6 SERIES 4.0VA											
Product Series	Primary Voltage (V)	Secondary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)		
4.0VA	115		630 VB381S-06040	6	667	8.9	T 70 B	28.3	153		
			500 VB381S-07040	7.2	556	10.7	T 70 B	28.3	153		
			400 VB381S-09040	9	444	12.6	T 70 B	28.3	153		
			400 VB381S-10040	10	400	14	T 70 B	28.3	153		
			315 VB381S-12040	12	333	16.4	T 70 B	28.3	153		
			250 VB381S-15040	15	267	21	T 70 B	28.3	153		
			200 VB381S-18040	18	222	24.3	T 70 B	28.3	153		
			160 VB381S-24040	24	167	32.5	T 70 B	28.3	153		
			315 VB381D-06040	6	2×333	2×8.9	T 70 B	28.3	153		
			250 VB381D-07040	7.2	2×278	2×10.7	T 70 B	28.3	153		
			200 VB381D-09040	9	2×222	2×12.6	T 70 B	28.3	153		
			200 VB381D-10040	10	2×200	2×14	T 70 B	28.3	153		
			160 VB381D-12040	12	2×167	2×16.4	T 70 B	28.3	153		
			125 VB381D-15040	15	2×133	2×21	T 70 B	28.3	153		
			100 VB381D-18040	18	2×111	2×24.3	T 70 B	28.3	153		
	230		630 VB382S-06040	6	667	8.9	T 70 B	28.3	153		
			500 VB382S-07040	7.2	556	10.7	T 70 B	28.3	153		
			400 VB382S-09040	9	444	12.6	T 70 B	28.3	153		
			400 VB382S-10040	10	400	14	T 70 B	28.3	153		
			315 VB382S-12040	12	333	16.4	T 70 B	28.3	153		
			250 VB382S-15040	15	267	21	T 70 B	28.3	153		
			200 VB382S-18040	18	222	24.3	T 70 B	28.3	153		
			160 VB382S-24040	24	167	32.5	T 70 B	28.3	153		
			315 VB382D-06040	6	2×333	2×8.9	T 70 B	28.3	153		
			250 VB382D-07040	7.2	2×278	2×10.7	T 70 B	28.3	153		
			200 VB382D-09040	9	2×222	2×12.6	T 70 B	28.3	153		
			200 VB382D-10040	10	2×200	2×14	T 70 B	28.3	153		
			160 VB382D-12040	12	2×167	2×16.4	T 70 B	28.3	153		
		400		125 VB382D-15040	15	2×133	2×21	T 70 B	28.3	153	
				100 VB382D-18040	18	2×111	2×24.3	T 70 B	28.3	153	
	630 VB383S-06040		6	667	8.9	T 70 B	28.3	153			
	500 VB383S-07040		7.2	556	10.7	T 70 B	28.3	153			
	400 VB383S-09040		9	444	12.6	T 70 B	28.3	153			
	400 VB383S-10040		10	400	14	T 70 B	28.3	153			
	315 VB383S-12040		12	333	16.4	T 70 B	28.3	153			
	250 VB383S-15040		15	267	21	T 70 B	28.3	153			
	200 VB383S-18040		18	222	24.3	T 70 B	28.3	153			
	160 VB383S-24040		24	167	32.5	T 70 B	28.3	153			
	315 VB383D-06040		6	2×333	2×8.9	T 70 B	28.3	153			
	250 VB383D-07040		7.2	2×278	2×10.7	T 70 B	28.3	153			
	200 VB383D-09040		9	2×222	2×12.6	T 70 B	28.3	153			
	200 VB383D-10040		10	2×200	2×14	T 70 B	28.3	153			
115 (Parallel) Or 230 (Series)			160 VB383D-12040	12	2×167	2×16.4	T 70 B	28.3	153		
		125 VB383D-15040	15	2×133	2×21	T 70 B	28.3	153			
		100 VB383D-18040	18	2×111	2×24.3	T 70 B	28.3	153			
		630 VB384S-06040	6	667	8.9	T 70 B	28.3	153			
		500 VB384S-07040	7.2	556	10.7	T 70 B	28.3	153			
		400 VB384S-09040	9	444	12.6	T 70 B	28.3	153			
		400 VB384S-10040	10	400	14	T 70 B	28.3	153			
		315 VB384S-12040	12	333	16.4	T 70 B	28.3	153			
		250 VB384S-15040	15	267	21	T 70 B	28.3	153			
		200 VB384S-18040	18	222	24.3	T 70 B	28.3	153			
		160 VB384S-24040	24	167	32.5	T 70 B	28.3	153			
		315 VB384D-06040	6	2×333	2×8.9	T 70 B	28.3	153			
		250 VB384D-07040	7.2	2×278	2×10.7	T 70 B	28.3	153			
		200 VB384D-09040	9	2×222	2×12.6	T 70 B	28.3	153			
		200 VB384D-10040	10	2×200	2×14	T 70 B	28.3	153			
	160 VB384D-12040	12	2×167	2×16.4	T 70 B	28.3	153				
	125 VB384D-15040	15	2×133	2×21	T 70 B	28.3	153				
	100 VB384D-18040	18	2×111	2×24.3	T 70 B	28.3	153				


ENCAPSULATED TRANSFORMER 密封变压器									
FEATURES				产品特点					
. Frequency 50/60 Hz				. 频率: 50/60 Hz					
. Temperature Class Class B (130° C)				. 温度等级: B级 (130° C)					
. Ambient Temperature (ta) 70° C				. 环境温度: (ta) 70° C					
. Resins Class B IEC85 (20,000H Testing to IEC216)				. 胶温度等级: B级 附合IEC85标准 (通过 20,000小时 IEC216标准)					
. Vacuum Potting				. 真空灌胶					
. Flammability Class UL94 V-0				. 材料阻燃等级: UL94 V-0					
. Dielectric Strength 4200Vrms				. 介电强度: 4200Vrms					
. Standard CE, CQC				. 标准: CE, CQC					
. Conforms EN61558, EN60950, UL1585, UL506				. 符合EN61558, EN60950, UL1585, UL506					
. 200%Tested Production				. 产线200%全检					
OUTLINE DIMENSIONS 外形尺寸				ELECTRICAL SCHEMATIC 电气原理图					
EI42-14.8 SERIES 5.0VA									
Product Series	Primary Voltage (V)	Secondary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
115	800		VB421S-06050	6	884	8.9	T 70 B	33	200
	630		VB421S-07050	7.2	695	10.7	T 70 B	33	200
	500		VB421S-09050	9	556	12.6	T 70 B	33	200
	500		VB421S-10050	10	500	14	T 70 B	33	200
	400		VB421S-12050	12	417	16.4	T 70 B	33	200
	315		VB421S-15050	15	333	21	T 70 B	33	200
	315		VB421S-18050	18	278	24.3	T 70 B	33	200
	200		VB421S-24050	24	208	32.5	T 70 B	33	200
	400		VB421D-06050	6	2x417	2x8.9	T 70 B	33	200
	315		VB421D-07050	7.2	2x348	2x10.7	T 70 B	33	200
	315		VB421D-09050	9	2x278	2x12.6	T 70 B	33	200
	250		VB421D-10050	10	2x250	2x14	T 70 B	33	200
	200		VB421D-12050	12	2x209	2x16.4	T 70 B	33	200
	160		VB421D-15050	15	2x167	2x21	T 70 B	33	200
	125		VB421D-18050	18	2x139	2x24.3	T 70 B	33	200
	800		VB422S-06050	6	884	8.9	T 70 B	33	200
	630		VB422S-07050	7.2	695	10.7	T 70 B	33	200
	500		VB422S-09050	9	556	12.6	T 70 B	33	200
	500		VB422S-10050	10	500	14	T 70 B	33	200
	400		VB422S-12050	12	417	16.4	T 70 B	33	200
	315		VB422S-15050	15	333	21	T 70 B	33	200
	315		VB422S-18050	18	278	24.3	T 70 B	33	200
	200		VB422S-24050	24	208	32.5	T 70 B	33	200
	400		VB422D-06050	6	2x417	2x8.9	T 70 B	33	200
315		VB422D-07050	7.2	2x348	2x10.7	T 70 B	33	200	
315		VB422D-09050	9	2x278	2x12.6	T 70 B	33	200	
250		VB422D-10050	10	2x250	2x14	T 70 B	33	200	
200		VB422D-12050	12	2x209	2x16.4	T 70 B	33	200	
160		VB422D-15050	15	2x167	2x21	T 70 B	33	200	
125		VB422D-18050	18	2x139	2x24.3	T 70 B	33	200	
230	800		VB423S-06050	6	884	8.9	T 70 B	33	200
	630		VB423S-07050	7.2	695	10.7	T 70 B	33	200
	500		VB423S-09050	9	556	12.6	T 70 B	33	200
	500		VB423S-10050	10	500	14	T 70 B	33	200
	400		VB423S-12050	12	417	16.4	T 70 B	33	200
	315		VB423S-15050	15	333	21	T 70 B	33	200
	315		VB423S-18050	18	278	24.3	T 70 B	33	200
	200		VB423S-24050	24	208	32.5	T 70 B	33	200
	400		VB423D-06050	6	2x417	2x8.9	T 70 B	33	200
	315		VB423D-07050	7.2	2x348	2x10.7	T 70 B	33	200
	315		VB423D-09050	9	2x278	2x12.6	T 70 B	33	200
	250		VB423D-10050	10	2x250	2x14	T 70 B	33	200
	200		VB423D-12050	12	2x209	2x16.4	T 70 B	33	200
	160		VB423D-15050	15	2x167	2x21	T 70 B	33	200
	125		VB423D-18050	18	2x139	2x24.3	T 70 B	33	200
	800		VB424S-06050	6	884	8.9	T 70 B	33	200
	630		VB424S-07050	7.2	695	10.7	T 70 B	33	200
	500		VB424S-09050	9	556	12.6	T 70 B	33	200
	500		VB424S-10050	10	500	14	T 70 B	33	200
	400		VB424S-12050	12	417	16.4	T 70 B	33	200
	315		VB424S-15050	15	333	21	T 70 B	33	200
	315		VB424S-18050	18	278	24.3	T 70 B	33	200
	200		VB424S-24050	24	208	32.5	T 70 B	33	200
	400		VB424D-06050	6	2x417	2x8.9	T 70 B	33	200
315		VB424D-07050	7.2	2x348	2x10.7	T 70 B	33	200	
315		VB424D-09050	9	2x278	2x12.6	T 70 B	33	200	
250		VB424D-10050	10	2x250	2x14	T 70 B	33	200	
200		VB424D-12050	12	2x209	2x16.4	T 70 B	33	200	
160		VB424D-15050	15	2x167	2x21	T 70 B	33	200	
125		VB424D-18050	18	2x139	2x24.3	T 70 B	33	200	

FEATURES

- ### 产品特点


- ## OUTLINE DIMENSIONS 外形尺寸

ELECTRICAL SCHEMATIC 电气原理图





EI42-14.8 SERIES 6.0VA

Product Series	Primary Voltage (V)	Secondary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage V(I)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)	
6.0VA	115	1000	VB421S-06000	6	1000	8.9	T 70 B	33	200	
		800	VB421S-07000	7.2	833	10.7	T 70 B	33	200	
		630	VB421S-09000	9	667	12.6	T 70 B	33	200	
		630	VB421S-10000	10	600	14	T 70 B	33	200	
		500	VB421S-12000	12	500	16.4	T 70 B	33	200	
		400	VB421S-15000	15	400	21	T 70 B	33	200	
		315	VB421S-18000	18	334	24.3	T 70 B	33	200	
		250	VB421S-24000	24	250	30.8	T 70 B	33	200	
		500	VB421D-06000	6	2x500	2x8.9	T 70 B	33	200	
		400	VB421D-07000	7.2	2x416	2x10.7	T 70 B	33	200	
		315	VB421D-09000	9	2x333	2x12.6	T 70 B	33	200	
		315	VB421D-10000	10	2x300	2x14	T 70 B	33	200	
		250	VB421D-12000	12	2x250	2x16.4	T 70 B	33	200	
		200	VB421D-15000	15	2x200	2x21	T 70 B	33	200	
		160	VB421D-18000	18	2x167	2x24.3	T 70 B	33	200	
		230	1000	VB422S-06000	6	1000	8.9	T 70 B	33	200
			800	VB422S-07000	7.2	833	10.7	T 70 B	33	200
			630	VB422S-09000	9	667	12.6	T 70 B	33	200
	630		VB422S-10000	10	600	14	T 70 B	33	200	
	500		VB422S-12000	12	500	16.4	T 70 B	33	200	
	400		VB422S-15000	15	400	21	T 70 B	33	200	
	315		VB422S-18000	18	334	24.3	T 70 B	33	200	
	250		VB422S-24000	24	250	30.8	T 70 B	33	200	
	500		VB422D-06000	6	2x500	2x8.9	T 70 B	33	200	
	400		VB422D-07000	7.2	2x416	2x10.7	T 70 B	33	200	
	315		VB422D-09000	9	2x333	2x12.6	T 70 B	33	200	
	315		VB422D-10000	10	2x300	2x14	T 70 B	33	200	
	250		VB422D-12000	12	2x250	2x16.4	T 70 B	33	200	
	200		VB422D-15000	15	2x200	2x21	T 70 B	33	200	
	160		VB422D-18000	18	2x167	2x24.3	T 70 B	33	200	
	400		1000	VB423S-06000	6	1000	8.9	T 70 B	33	200
			800	VB423S-07000	7.2	833	10.7	T 70 B	33	200
			630	VB423S-09000	9	667	12.6	T 70 B	33	200
		630	VB423S-10000	10	600	14	T 70 B	33	200	
		500	VB423S-12000	12	500	16.4	T 70 B	33	200	
		400	VB423S-15000	15	400	21	T 70 B	33	200	
		315	VB423S-18000	18	334	24.3	T 70 B	33	200	
		250	VB423S-24000	24	250	30.8	T 70 B	33	200	
		500	VB423D-06000	6	2x500	2x8.9	T 70 B	33	200	
		400	VB423D-07000	7.2	2x416	2x10.7	T 70 B	33	200	
		315	VB423D-09000	9	2x333	2x12.6	T 70 B	33	200	
		315	VB423D-10000	10	2x300	2x14	T 70 B	33	200	
		250	VB423D-12000	12	2x250	2x16.4	T 70 B	33	200	
		200	VB423D-15000	15	2x200	2x21	T 70 B	33	200	
		160	VB423D-18000	18	2x167	2x24.3	T 70 B	33	200	
		115 (Parallel) Or 230 (Series)	1000	VB424S-06000	6	1000	8.9	T 70 B	33	200
			800	VB424S-07000	7.2	833	10.7	T 70 B	33	200
			630	VB424S-09000	9	667	12.6	T 70 B	33	200
630	VB424S-10000		10	600	14	T 70 B	33	200		
500	VB424S-12000		12	500	16.4	T 70 B	33	200		
400	VB424S-15000		15	400	21	T 70 B	33	200		
315	VB424S-18000		18	334	24.3	T 70 B	33	200		
250	VB424S-24000		24	250	30.8	T 70 B	33	200		
500	VB424D-06000		6	2x500	2x8.9	T 70 B	33	200		
400	VB424D-07000		7.2	2x416	2x10.7	T 70 B	33	200		
315	VB424D-09000		9	2x333	2x12.6	T 70 B	33	200		
315	VB424D-10000		10	2x300	2x14	T 70 B	33	200		

ENCAPSULATED TRANSFORMER 密封变压器									
FEATURES					产品特点				
. Frequency 50/60 Hz					. 频率: 50/60 Hz				
. Temperature Class Class B (130° C)					. 温度等级: B级 (130° C)				
. Ambient Temperature (ta) 50° C					. 环境温度: (ta) 50° C				
. Resins Class B IEC85 (20,000H Testing to IEC216)					. 胶温度等级: B级 符合IEC85标准 (通过 20,000小时 IEC216标准)				
. Vacuum Potting					. 真空灌胶				
. Flammability Class UL94 V-0					. 材料阻燃等级: UL94 V-0				
. Dielectric Strength 4200Vrms					. 介电强度: 4200Vrms				
. Standard CE, CQC					. 标准: CE, CQC				
. Conforms EN61558, EN60950, UL1585, UL506					. 符合EN61558, EN60950, UL1585, UL506				
. 200%Tested Production					. 产线200%全检				
OUTLINE DIMENSIONS 外形尺寸					ELECTRICAL SCHEMATIC 电气原理图				
									
EI48-16.8 SERIES 8.0VA									
Product Series	Primary Voltage (V)	primary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
	115		100 VB481S-06080	6	1333	8.5	T 70 B	35.5	275
			100 VB481S-07080	7.2	1111	9.5	T 70 B	35.5	275
			100 VB481S-09080	9	889	11.5	T 70 B	35.5	275
			100 VB481S-10080	10	800	12.5	T 70 B	35.5	275
			100 VB481S-12080	12	667	14.5	T 70 B	35.5	275
			100 VB481S-15080	15	533	17.5	T 70 B	35.5	275
			100 VB481S-18080	18	444	20.5	T 70 B	35.5	275
			100 VB481S-20080	20	400	22.5	T 70 B	35.5	275
			100 VB481S-24080	24	333	26.5	T 70 B	35.5	275
			100 VB481D-06080	6	2÷667	2÷8.5	T 70 B	35.5	275
			100 VB481D-07080	7.2	2÷556	2÷9.5	T 70 B	35.5	275
			100 VB481D-09080	9	2÷444	2÷11.5	T 70 B	35.5	275
			100 VB481D-10080	10	2÷400	2÷12.5	T 70 B	35.5	275
			100 VB481D-12080	12	2÷333	2÷14.5	T 70 B	35.5	275
			100 VB481D-15080	15	2÷266	2÷17.5	T 70 B	35.5	275
			100 VB481D-18080	18	2÷222	2÷20.5	T 70 B	35.5	275
	230		50 VB482S-06080	6	1333	8.5	T 70 B	35.5	275
			50 VB482S-07080	7.2	1111	9.5	T 70 B	35.5	275
			50 VB482S-09080	9	889	11.5	T 70 B	35.5	275
			50 VB482S-10080	10	800	12.5	T 70 B	35.5	275
			50 VB482S-12080	12	667	14.5	T 70 B	35.5	275
			50 VB482S-15080	15	533	17.5	T 70 B	35.5	275
			50 VB482S-18080	18	444	20.5	T 70 B	35.5	275
			50 VB482S-20080	20	400	22.5	T 70 B	35.5	275
			50 VB482S-24080	24	333	26.5	T 70 B	35.5	275
			50 VB482D-06080	6	2÷667	2÷8.5	T 70 B	35.5	275
			50 VB482D-07080	7.2	2÷556	2÷9.5	T 70 B	35.5	275
			50 VB482D-09080	9	2÷444	2÷11.5	T 70 B	35.5	275
			50 VB482D-10080	10	2÷400	2÷12.5	T 70 B	35.5	275
			50 VB482D-12080	12	2÷333	2÷14.5	T 70 B	35.5	275
			50 VB482D-15080	15	2÷266	2÷17.5	T 70 B	35.5	275
			50 VB482D-18080	18	2÷222	2÷20.5	T 70 B	35.5	275
	400		32 VB483S-06080	6	1333	8.5	T 70 B	35.5	275
			32 VB483S-07080	7.2	1111	9.5	T 70 B	35.5	275
			32 VB483S-09080	9	889	11.5	T 70 B	35.5	275
			32 VB483S-10080	10	800	12.5	T 70 B	35.5	275
			32 VB483S-12080	12	667	14.5	T 70 B	35.5	275
			32 VB483S-15080	15	533	17.5	T 70 B	35.5	275
			32 VB483S-18080	18	444	20.5	T 70 B	35.5	275
			32 VB483S-20080	20	400	22.5	T 70 B	35.5	275
			32 VB483S-24080	24	333	26.5	T 70 B	35.5	275
			32 VB483D-06080	6	2÷667	2÷8.5	T 70 B	35.5	275
			32 VB483D-07080	7.2	2÷556	2÷9.5	T 70 B	35.5	275
			32 VB483D-09080	9	2÷444	2÷11.5	T 70 B	35.5	275
			32 VB483D-10080	10	2÷400	2÷12.5	T 70 B	35.5	275
			32 VB483D-12080	12	2÷333	2÷14.5	T 70 B	35.5	275
			32 VB483D-15080	15	2÷266	2÷17.5	T 70 B	35.5	275
			32 VB483D-18080	18	2÷222	2÷20.5	T 70 B	35.5	275
	115 (Parallel) Or 230 (Series)		1000r50 VB482S-06080	6	1333	8.5	T 70 B	35.5	275
			1000r50 VB482S-07080	7.2	1111	9.5	T 70 B	35.5	275
			1000r50 VB482S-09080	9	889	11.5	T 70 B	35.5	275
			1000r50 VB482S-10080	10	800	12.5	T 70 B	35.5	275
			1000r50 VB482S-12080	12	667	14.5	T 70 B	35.5	275
			1000r50 VB482S-15080	15	533	17.5	T 70 B	35.5	275
			1000r50 VB482S-18080	18	444	20.5	T 70 B	35.5	275
			1000r50 VB482S-20080	20	400	22.5	T 70 B	35.5	275
			1000r50 VB482S-24080	24	333	26.5	T 70 B	35.5	275
			1000r50 VB482D-06080	6	2÷667	2÷8.5	T 70 B	35.5	275
			1000r50 VB482D-07080	7.2	2÷556	2÷9.5	T 70 B	35.5	275
			1000r50 VB482D-09080	9	2÷444	2÷11.5	T 70 B	35.5	275
			1000r50 VB482D-10080	10	2÷400	2÷12.5	T 70 B	35.5	275
			1000r50 VB482D-12080	12	2÷333	2÷14.5	T 70 B	35.5	275
			1000r50 VB482D-15080	15	2÷266	2÷17.5	T 70 B	35.5	275
			1000r50 VB482D-18080	18	2÷222	2÷20.5	T 70 B	35.5	275

ENCAPSULATED TRANSFORMER 密封变压器									
FEATURES					产品特点				
. Frequency 50/60 Hz					. 频率: 50/60 Hz				
. Temperature Class Class B (130° C)					. 温度等级: B级 (130° C)				
. Ambient Temperature (ta) 50° C					. 环境温度: (ta) 50° C				
. Resins Class B IEC86 (20,000H Testing to IEC216)					. 胶温度等级: B级 符合IEC85标准 (通过 20,000小时 IEC216标准)				
. Vacuum Potting					. 真空灌胶				
. Flammability Class UL94 V-0					. 材料阻燃等级: UL94 V-0				
. Dielectric Strength 4200Vrms					. 介电强度: 4200Vrms				
. Standard CE, CQC					. 标准: CE, CQC				
. Conforms EN61558, EN60950, UL1585, UL506					. 符合EN61558, EN60950, UL1585, UL506				
. 200% Tested Production					. 产线200%全检				
OUTLINE DIMENSIONS 外形尺寸					ELECTRICAL SCHEMATIC 电气原理图				
EI48-16.8 SERIES 10.0VA									
Product Series	Primary Voltage (V)	primary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
10.0VA	115		125 VB481S-06100	6	1667	7.6	T 50 B	35.5	285
			125 VB481S-07100	7.2	1389	8.9	T 50 B	35.5	285
			125 VB481S-09100	9	1111	11.4	T 50 B	35.5	285
			125 VB481S-10100	10	1000	12.5	T 50 B	35.5	285
			125 VB481S-12100	12	833	15.2	T 50 B	35.5	285
			125 VB481S-15100	15	667	18.9	T 50 B	35.5	285
			125 VB481S-18100	18	556	22.3	T 50 B	35.5	285
			125 VB481S-20100	20	500	24.5	T 50 B	35.5	285
			125 VB481S-24100	24	417	29.4	T 50 B	35.5	285
			125 VB481D-06100	6	2*833	2*7.6	T 50 B	35.5	285
			125 VB481D-07100	7.2	2*695	2*8.9	T 50 B	35.5	285
			125 VB481D-09100	9	2*556	2*11.4	T 50 B	35.5	285
			125 VB481D-10100	10	2*500	2*12.5	T 50 B	35.5	285
			125 VB481D-12100	12	2*417	2*15.2	T 50 B	35.5	285
			125 VB481D-15100	15	2*333	2*18.9	T 50 B	35.5	285
			125 VB481D-18100	18	2*258	2*22.3	T 50 B	35.5	285
	230		63 VB482S-06100	6	1667	7.6	T 50 B	35.5	285
			63 VB482S-07100	7.2	1389	8.9	T 50 B	35.5	285
			63 VB482S-09100	9	1111	11.4	T 50 B	35.5	285
			63 VB482S-10100	10	1000	12.5	T 50 B	35.5	285
			63 VB482S-12100	12	833	15.2	T 50 B	35.5	285
			63 VB482S-15100	15	667	18.9	T 50 B	35.5	285
			63 VB482S-18100	18	556	22.3	T 50 B	35.5	285
			63 VB482S-20100	20	500	24.5	T 50 B	35.5	285
			63 VB482S-24100	24	417	29.4	T 50 B	35.5	285
			63 VB482D-06100	6	2*833	2*7.6	T 50 B	35.5	285
			63 VB482D-07100	7.2	2*695	2*8.9	T 50 B	35.5	285
			63 VB482D-09100	9	2*556	2*11.4	T 50 B	35.5	285
			63 VB482D-10100	10	2*500	2*12.5	T 50 B	35.5	285
			63 VB482D-12100	12	2*417	2*15.2	T 50 B	35.5	285
			63 VB482D-15100	15	2*333	2*18.9	T 50 B	35.5	285
			63 VB482D-18100	18	2*258	2*22.3	T 50 B	35.5	285
	400		32 VB483S-06100	6	1667	7.6	T 50 B	35.5	285
			32 VB483S-07100	7.2	1389	8.9	T 50 B	35.5	285
			32 VB483S-09100	9	1111	11.4	T 50 B	35.5	285
			32 VB483S-10100	10	1000	12.5	T 50 B	35.5	285
			32 VB483S-12100	12	833	15.2	T 50 B	35.5	285
			32 VB483S-15100	15	667	18.9	T 50 B	35.5	285
			32 VB483S-18100	18	556	22.3	T 50 B	35.5	285
			32 VB483S-20100	20	500	24.5	T 50 B	35.5	285
			32 VB483S-24100	24	417	29.4	T 50 B	35.5	285
			32 VB483D-06100	6	2*833	2*7.6	T 50 B	35.5	285
			32 VB483D-07100	7.2	2*695	2*8.9	T 50 B	35.5	285
			32 VB483D-09100	9	2*556	2*11.4	T 50 B	35.5	285
			32 VB483D-10100	10	2*500	2*12.5	T 50 B	35.5	285
			32 VB483D-12100	12	2*417	2*15.2	T 50 B	35.5	285
			32 VB483D-15100	15	2*333	2*18.9	T 50 B	35.5	285
			32 VB483D-18100	18	2*258	2*22.3	T 50 B	35.5	285
	115 (Parallel) Or 230 (Series)		125or63 VB482S-06100	6	1667	7.6	T 50 B	35.5	285
			125or63 VB482S-07100	7.2	1389	8.9	T 50 B	35.5	285
			125or63 VB482S-09100	9	1111	11.4	T 50 B	35.5	285
			125or63 VB482S-10100	10	1000	12.5	T 50 B	35.5	285
			125or63 VB482S-12100	12	833	15.2	T 50 B	35.5	285
			125or63 VB482S-15100	15	667	18.9	T 50 B	35.5	285
			125or63 VB482S-18100	18	556	22.3	T 50 B	35.5	285
			125or63 VB482S-20100	20	500	24.5	T 50 B	35.5	285
			125or63 VB482S-24100	24	417	29.4	T 50 B	35.5	285
			125or63 VB482D-06100	6	2*833	2*7.6	T 50 B	35.5	285
			125or63 VB482D-07100	7.2	2*695	2*8.9	T 50 B	35.5	285
			125or63 VB482D-09100	9	2*556	2*11.4	T 50 B	35.5	285
			125or63 VB482D-10100	10	2*500	2*12.5	T 50 B	35.5	285
			125or63 VB482D-12100	12	2*417	2*15.2	T 50 B	35.5	285
			125or63 VB482D-15100	15	2*333	2*18.9	T 50 B	35.5	285
			125or63 VB482D-18100	18	2*258	2*22.3	T 50 B	35.5	285

ENCAPSULATED TRANSFORMER 密封变压器									
FEATURES				产品特点					
. Frequency 50/60 Hz				. 频率: 50/60 Hz					
. Temperature Class Class B (130° C)				. 温度等级: B级 (130° C)					
. Ambient Temperature (ta) 50° C				. 环境温度: (ta) 50° C					
. Resins Class B IEC85 (20,000H Testing to IEC216)				. 胶温等级: B级 符合IEC85标准 (通过 20,000小时 IEC216标准)					
. Vacuum Potting				. 真空灌胶					
. Flammability Class UL94 V-0				. 材料阻燃等级: UL94 V-0					
. Dielectric Strength 4200Vrms				. 介电强度: 4200Vrms					
. Standard CE, CQC				. 标准: CE, CQC					
. Conforms EN61558, EN60950, UL1585, UL506				. 符合EN61558, EN60950, UL1585, UL506					
. 200% Tested Production				. 产线200%全检					
OUTLINE DIMENSIONS 外形尺寸				ELECTRICAL SCHEMATIC 电气原理图					
									
EI48-25 SERIES 15.0VA									
Product Series	Primary Voltage (V)	primary protection (mA)	Part Number	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)(max)	Ambient Temperature (°C)	Dimension H MAX (mm)	Weight Approx (g)
15.0VA	115		250 VB481S-06150	6	2500	9.8	T 70 B	45.5	400
			250 VB481S-07150	7.2	2083	10.8	T 70 B	45.5	400
			250 VB481S-09150	9	1667	12.8	T 70 B	45.5	400
			250 VB481S-10150	10	1500	13.5	T 70 B	45.5	400
			250 VB481S-12150	12	1250	15.5	T 70 B	45.5	400
			250 VB481S-15150	15	1000	18.5	T 70 B	45.5	400
			250 VB481S-18150	18	833	21.5	T 70 B	45.5	400
			250 VB481S-20150	20	750	23.5	T 70 B	45.5	400
			250 VB481S-24150	24	625	27.5	T 70 B	45.5	400
			250 VB481D-06150	6	2×1250	2×7.6	T 70 B	45.5	400
			250 VB481D-07150	7.2	2×1042	2×8.9	T 70 B	45.5	400
			250 VB481D-09150	9	2×833	2×11.4	T 70 B	45.5	400
			250 VB481D-10150	10	2×750	2×12.5	T 70 B	45.5	400
			250 VB481D-12150	12	2×625	2×15.2	T 70 B	45.5	400
			250 VB481D-15150	15	2×500	2×18.9	T 70 B	45.5	400
			250 VB481D-18150	18	2×417	2×22.3	T 70 B	45.5	400
	230		100 VB482S-06150	6	2500	9.8	T 70 B	45.5	400
			100 VB482S-07150	7.2	2083	10.8	T 70 B	45.5	400
			100 VB482S-09150	9	1667	12.8	T 70 B	45.5	400
			100 VB482S-10150	10	1500	13.5	T 70 B	45.5	400
			100 VB482S-12150	12	1250	15.5	T 70 B	45.5	400
			100 VB482S-15150	15	1000	18.5	T 70 B	45.5	400
			100 VB482S-18150	18	833	21.5	T 70 B	45.5	400
			100 VB482S-20150	20	750	23.5	T 70 B	45.5	400
			100 VB482S-24150	24	625	27.5	T 70 B	45.5	400
			100 VB482D-06150	6	2×1250	2×7.6	T 70 B	45.5	400
			100 VB482D-07150	7.2	2×1042	2×8.9	T 70 B	45.5	400
			100 VB482D-09150	9	2×833	2×11.4	T 70 B	45.5	400
			100 VB482D-10150	10	2×750	2×12.5	T 70 B	45.5	400
			100 VB482D-12150	12	2×625	2×15.2	T 70 B	45.5	400
			100 VB482D-15150	15	2×500	2×18.9	T 70 B	45.5	400
			100 VB482D-18150	18	2×417	2×22.3	T 70 B	45.5	400
15.0VA	400		50 VB483S-06150	6	2500	9.8	T 70 B	45.5	400
			50 VB483S-07150	7.2	2083	10.8	T 70 B	45.5	400
			50 VB483S-09150	9	1667	12.8	T 70 B	45.5	400
			50 VB483S-10150	10	1500	13.5	T 70 B	45.5	400
			50 VB483S-12150	12	1250	15.5	T 70 B	45.5	400
			50 VB483S-15150	15	1000	18.5	T 70 B	45.5	400
			50 VB483S-18150	18	833	21.5	T 70 B	45.5	400
			50 VB483S-20150	20	750	23.5	T 70 B	45.5	400
			50 VB483S-24150	24	625	27.5	T 70 B	45.5	400
			50 VB483D-06150	6	2×1250	2×7.6	T 70 B	45.5	400
			50 VB483D-07150	7.2	2×1042	2×8.9	T 70 B	45.5	400
			50 VB483D-09150	9	2×833	2×11.4	T 70 B	45.5	400
			50 VB483D-10150	10	2×750	2×12.5	T 70 B	45.5	400
			50 VB483D-12150	12	2×625	2×15.2	T 70 B	45.5	400
			50 VB483D-15150	15	2×500	2×18.9	T 70 B	45.5	400
			50 VB483D-18150	18	2×417	2×22.3	T 70 B	45.5	400
	115 (Parallel) Or 230 (Series)		250or100 VB482S-06150	6	2500	9.8	T 70 B	45.5	400
			250or100 VB482S-07150	7.2	2083	10.8	T 70 B	45.5	400
			250or100 VB482S-09150	9	1667	12.8	T 70 B	45.5	400
			250or100 VB482S-10150	10	1500	13.5	T 70 B	45.5	400
			250or100 VB482S-12150	12	1250	15.5	T 70 B	45.5	400
			250or100 VB482S-15150	15	1000	18.5	T 70 B	45.5	400
			250or100 VB482S-18150	18	833	21.5	T 70 B	45.5	400
			250or100 VB482S-20150	20	750	23.5	T 70 B	45.5	400
			250or100 VB482S-24150	24	625	27.5	T 70 B	45.5	400
			250or100 VB482D-06150	6	2×1250	2×7.6	T 70 B	45.5	400
			250or100 VB482D-07150	7.2	2×1042	2×8.9	T 70 B	45.5	400
			250or100 VB482D-09150	9	2×833	2×11.4	T 70 B	45.5	400
			250or100 VB482D-10150	10	2×750	2×12.5	T 70 B	45.5	400
			250or100 VB482D-12150	12	2×625	2×15.2	T 70 B	45.5	400
			250or100 VB482D-15150	15	2×500	2×18.9	T 70 B	45.5	400
			250or100 VB482D-18150	18	2×417	2×22.3	T 70 B	45.5	400